



STEELE[®]
products

SP-GG200


Compact Generator



2000 Watts


- 3 HP OHV engine
- Runs 9 hours at 1/2 load
- Operating noise 65 dB
- 2-AC 120V outlets, 1-DC 12 V output
- Lightweight, compact size
- EPA approved

Peak power	2000w
Rated power	1400w
AC rated current	11.6A
DC rated voltage	12V
DC rated current	8.3A
Fuel tank	1.32 Gallons
Fuel type	Unleaded Gasoline
Start	Recoil Start




This Unit Will Operate

Water Well Pump: 3000 Watts	0 dB
Furnace Fan 1/3 HP: 2100 Watts	10 dB
Refrigerator or Freezer: 2900 Watts	20 dB
Microwave Oven: 800 Watts	30 dB
Light Bulb: 60 watts	40 dB



Examples of sound pressure levels:

Threshold of hearing	0 dB
Anechoic Chamber (Soundproof room)	10 dB
Extremely quiet recording studio	20 dB
Soft Whisper	30 dB
Quiet Auditorium	40 dB
Average house	50 dB
Average Conversation	60 dB
SP-GG200	65 dB
Alarm Clock	70 dB
Cabin of a Jet Airplane	80 dB
Heavy street traffic	90 dB
Loud Classical Music	100 dB
Soundtrack from a movie	110 dB
Live Rock Music	120 dB
Jet Airplane and Gunshots	130 dB
Threshold of Pain	140 dB



9 Hour Run Time

Model	SP-GG200
Weight	59.4 lbs
Dimensions	18.5"x14.5"x15.3"
UPC	8 52055 00566 6

www.steele-products.com